

## Dark Undercoat Paste

### General

It is used for improve to alive colors. It is a suitable, covering effect base that is applied to print dark base.

### Advantages

- Dark Undercoat Paste has high wash fastness and fixed room temperature.
- It is the product that gives the closest effect to abrasion at the points where the discharge paste is not wanted to be used.
- Suitable to ecological standards.

### Applications

- It can be fixed under room temperature.
- It is a suitable, covering effect base that is applied to print dark base.

### Usage

- It provides to print with the silk-screen that are made between 43-54 mesh
- It should be used with 50 – 70 Shore, U type.

### Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C /(+41)-(+86)°F of temperature.
- It should be consumed within 2 years after the production date.

### Technical Details



**Appearance**  
Paste



**Odor**  
Characteristic



**Color**  
Yellowish Trasparent



**Viscosity**  
[(77°F/25°C) sp: 7, rpm: 20 Brookfield] :  
60.000 - 70.000 [mPa.s]



**Density**  
1,3 g/cm (77°F / 25°C)



**pH**  
8,0 – 8,5



**Boiling Point**  
>100°C (212°F)



**Solubility**  
Soluble in water



**Explosion Hazard**  
Not explosive



**Packaging Information**  
Dark Undercoat Paste is packed in  
5/10/20/30/60 kg blue polyethylene  
cans.

### Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.